



ULTIMA HEAT REJECTION NATURAL 70

Ultima Heat Rejection Natural 70 film is crafted with a primary focus on enhancing film performance. This film stands out for its ability to deliver superior results by utilizing specialized nano dispersion technology. Designed to ensure maximum heat rejection and optical clarity, offering advanced comfort and performance without the use of metalized content.



WARRANTY

10 years Commercial &
Limited Lifetime Residential

CONSTRUCTION:

Thickness	2 mil
Metal	Metal Free
Adhesive	Pressure Sensitive

Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.

PLATINA

PERFORMANCE:

VLT	Visible Light Transmittance	66 %
VLR-E	Visible Light Reflectance	9 %
VLR-I	Visible Light Reflectance	10 %
TST	Total Solar Transmittance	35 %
TSR	Total Solar Reflectance	7 %
TSA	Total Solar Absorbance	58 %
UVR	Ultraviolet Rejected	> 99 %
TSER	Total Solar Energy Rejected	49 %
SC	Shading Coefficient	0.58
SHGC	Solar Heat Gain Coefficient	0.51
LE	Luminous Efficacy	1.14
GR	Glare Reduction	27 %
NIRB	NIR Blocking	91 ± 3.0%



9689 968 996